

# PACK SIB EVO 5.1.2

(3 x Sib Evo, 2 x Sib Evo DOLBY ATMOS®, 1 x Cub Evo)

## Product Data Sheet

The 5.1.2 Sib Evo pack generalises Dolby Atmos® standard which was mainly dedicated to professionals or cinema rooms. It opens the door to those who want to reproduce the effects of a true screening room, whatever in a living room or a dedicated room. The audio quality of our Sib Evo loudspeakers is impressive considering their size. The audio track will perfectly render the dialogue and full intensity of the action or emotion. This technology lies in the Atmos® effect, the reflexion of sound waves off the ceiling towards the listener using an extra speaker driver on top of the Dolby Atmos® speaker. All the key elements of the film are conveyed with extreme clarity and pitch-perfect precision, giving the spectator the impression of being right at the heart of the action. Sib Evo is the 'lifestyle' loudspeaker which fits with every interior.



### Key points

- A sound power without equivalent in the category.
- 'Design' loudspeakers perfectly integrated in every interior.
- Hi-fi and Home Cinema audio quality.
- Complete pack for an installation as easy as a 5.1 system.
- Dolby Atmos® technology reproducing vertical effects from the ceiling thanks to a vertical-firing 4" speaker driver.

**Accessories included:** 2 x Wall mount system

**In option:** Hip Evo stand

# PACK SIB EVO 5.1.2

(3 x Sib Evo, 2 x Sib Evo Dolby Atmos®, 1 x Cub Evo)

## Product Data Sheet

### Technical specifications

#### Sib EVO

Type of loudspeaker	Two-way compact bass-reflex loudspeaker
Speakers	5" (13cm) Polyflex woofer 3/4" (19mm) soft dome tweeter
Frequency response (+/-3dB)	70Hz to 25kHz
Low frequency point (-6dB)	66Hz
Sensibility (2.83V/1m)	90dB
Nominal Impedance	6 Ohms
Crossover Frequency	3.5kHz
Recommended Amplifier Power	25 - 200W
Dimensions (HxWxD)	9 <sup>15/16</sup> "x6 <sup>3/8</sup> "x6 <sup>3/8</sup> " (252x162x162mm)
Weight (unit)	4lbs (1.8kg)

#### Cub EVO

Type of loudspeaker	Active bass-reflex subwoofer
Speaker	8 <sup>1/4</sup> " (21cm) Polyflex woofer
Frequency response (+/-3dB)	35Hz - 150Hz
Cutoff frequency (-6dB)	30Hz
RCA input	Right, left LFE
Cut-off frequency	3.5kHz
Phase adjustment	Phase inverter 0° / 180°
Amplifier power	200W Class-D amplifier
Power mode	On / Autopower (0.5W)
Dimensions (H x W x D)	2" x 11 <sup>1/8</sup> " x 11 <sup>3/4</sup> " (305x282x299mm)
Weight (per unit)	17.5lbs (8kg)

#### Sib EVO Dolby Atmos®

	Front Channel	Atmos® Channel
Type	Two-way bass-reflex loudspeaker	Fullrange sealed loudspeaker
Speakers	5" (13cm) Polyflex woofer 3/4" (19mm) soft dome tweeter	4" (10cm) full-range speaker
Frequency Response (+/-3dB)	65Hz to 25kHz	90Hz to 20kHz
Low frequency point -6dB	60Hz	75Hz
Sensibility (2.83V/1m)	90dB	90dB
Nominal impedance	6 Ohms	6 Ohms
Crossover Frequency	3.5kHz	
Recommended Amplifier Power	25 - 200W	
Dimensions (HxWxD)	11 <sup>5/8</sup> "x7 <sup>11/16</sup> "x7 <sup>1/2</sup> " (295x195x190mm)	
Weight (unit)	7lbs (3.25 kg)	

Reference	Pack 5.1.2 Sib Evo Dolby Atmos™
Item code	ESIBPA5121
Packaging Dimension (LxPxH)	23 <sup>35/64</sup> "x15 <sup>5/32</sup> "x26 <sup>49/64</sup> " (59,8x38,5x68cm)
Net weight	58.4lbs (26.5kg)