

The Ultimate Positional Gaming Audio



GSX 1200 PRO

 **SENNHEISER**



GSX 1200 PRO

Designed for the competitive eSports arena, the GSX 1200 PRO audio amplifier features a groundbreaking 7.1. Virtual Surround Algorithm. Experience Surround Sound on a new level. Precise control of both game and communication sound, allowing separate adjustments and switch between headphones and speakers without unplugging cables. Get ready for the tournament and connect up to 8 GSX 1200 PROs together for hard-wired lag-free communication and control of inbound and outbound chat. It works with PC and Mac.

Benefits and Features:

- 7.1 Sennheiser Binaural Rendering Engine – the ultimate positional gaming audio
- Chat Link – connect up to 8 GSX 1200 PROs together for hard-wired lag-free communication
- Aluminium volume wheel and high-quality materials for superior performance
- Switch between your headset and speakers with the touch of a button
- Adjust game and communication audio separately
- Peace of mind – 2-year international warranty

Technical Data

GSX 1200 PRO

EAN No.	40 44155 21192 4
UPC No.	6 15104 27672 7
Art. No.	507080

General Data

USB standard	2.0 USB Full Speed & 1.0 USB Audio
Total harmonic distortion	0.005 % THD
Cable length	USB Cable: 1.2 m / Chat Cable: 2.0 m
Connector plugs	3.5 mm headset socket, 3.5 mm microphone socket, 3.5 mm loudspeaker socket, mini-USB socket, 2.5 mm chat interface socket A, 2.5 mm chat interface socket B
Delivery includes	GSX 1200 PRO audio amplifier, chat cable, USB cable, Quick Start Guide, Safety Guide
Warranty	2 years

Supported sample rates

Main Audio	7.1: 44.1 kHz @ 16 bit 7.1: 48.0 kHz @ 16 bit 2.0: 44.1 kHz @ 16 bit 2.0: 48.0 kHz @ 16 bit
Main Audio HD	2.0: 96.0 kHz @ 24 bit
Communication Audio	1.0: 16.0 kHz @ 16 bit

Audio outputs

Headphone:	DC coupled and dual rail power supply
Frequency response	0 – 48.0 kHz
Recommended headphone impedance	16 – 150 Ω
Max. output voltage	1 V RMS @ 32 Ω
Line out (AUX):	
Frequency response	1.5 – 48.0 kHz
Max. output voltage	1 V RMS @ 10 kΩ

Packaging

Dimensions product packaging (W x H x D)	143 x 70 x 139 mm
Weight of product and packaging	413 g
Dimension of Master carton (W x D x H)	378 x 284 x 156 mm
Units per Master carton	10
Languages	English, German, French, Spanish, Italian, Dutch and Portuguese